

Volkswagen Transporter T5 + T6

Theoretical ground clearance (unladen weight) depending on SEIKEL lift kit and tyre size

Tyre size	Standard ground clearance in mm	Tyre size		Installation SEIKEL ● lift kit	Theoretical ground clearance Middle of front axle in mm		Necessary kit/conversion			Possible treads	
		Standard size	Larger than standard		in mm	Extra height	Short SEIKEL axle transmission	Adjust wheel arches	Steering stop limit	A/T	M/T
Standard tyres				More ground clearance in mm than standard							
205/65 R16	180	●		●	210	+ 30					
215/65 R16	180	●		●	210	+ 30					
215/60 R17	180	●		●	210	+ 30					
235/55 R17	180	●		●	210	+ 30					
255/45 R18	180	●		●	210	+ 30					
Conversion sizes											
235/60 R16	180	identical		without	180	+/- 0				●	
235/60 R16	180	identical		●	210	+ 30				●	
225/70 R16			●	●	227	+ 47				●	
235/70 R16			●	●	234	+ 54				●	●
235/65 R17			●	●	234	+ 54			●	●	
255/55 R18			●	●	234	+ 54		●	●	●	
225/75 R16			●	●	238	+ 58	●			●	●
225/70 R17			●	●	238	+ 58	●			●	
235/70 R17			●	●	244	+ 64	●	●	●	●	
255/60 R18			●	●	245	+ 65	●	●	●	●	
245/75 R16			●	●	253	+ 73	●	●	●	●	●
245/70 R17			●	●	253	+ 73	●	●	●	●	●

- Minor conversion work
- Medium conversion work
- Major conversion work

Information not guaranteed, subject to error and change without notice.