

Volkswagen Amarok

Theoretical ground clearance (unladen weight) depending on SEIKEL lift kit and tyre size

On this basis we show you in this table the ground clearance you can expect after installing the SEIKEL lift kit and/or bigger tyres

Tyre size	Standard ground clearance in mm	Tyre size		Installation SEIKEL lift kit	Theoretical ground clearance Middle of front axle		Necessary kit / conversion			Possible treads	
		Standard size	Larger than standard		in mm	Extra height	Speedo test	Speedo adjustment	Steering stop limit	A/T	M/T
Standard tyres	WITHOUT drive train protection				More ground clearance in mm than standard						
205/80 R16	230	●		●	255	+ 25					
245/70 R16	230	●		●	255	+ 25				●	
245/65 R17	230	●		●	255	+ 25					
245/70 R17	230	●		●	255	+ 25				●	●
255/60 R18	230	●		●	255	+ 25					
255/55 R19	230	●		●	255	+ 25					
Conversion sizes											
225/75 R16	230	identical		without	230	+/- 0				●	
225/75 R16	230	identical		●	255	+ 25					
245/75 R16			●	●	265	+ 35	●			●	●
245/75 R17			●	●	280	+ 50		●		●	
265/70 R17			●	●	280	+ 50		●		●	●
265/65 R18			●	●	280	+ 50		●		●	
255/55 R20			●	●	265	+ 35		●		●	

Information not guaranteed, subject to error and change without notice.

SEIKEL GmbH - 02/2017